

## BLACK SEAL SILICONE

### HEAT-RESISTANT SEALANT

#### DESCRIPTION

Permanently elastic silicone-based sealant which is resistant to all weather influences. Has an extreme adhesion to steel, aluminium, ceramics, glass, wood, plastic and other materials. Ideal for sealing engine blocks, gearboxes, valve cover, oil sump, oil and water pump, heating installations, industrial and domestic furnaces, flue gas ducts, air conditioning units. Secure adhesion and sealing, both at ambient temperature and at high temperatures (up to + 250°C).

#### CHARACTERISTICS

- Very high initial adhesion.
- For indoor and outdoor use in all weather conditions.
- Fast curing, also at low temperatures.
- Isocyanate silicone and solvent-free.

#### APPLICATION

Specially developed for the bonding of a wide variety of materials, which are normally not or only very difficult to bond with each other. Ideal for bodywork applications, for sealing steel sheet transitions against rust and corrosion.

#### INSTRUCTIONS FOR USE

Apply Black Seal Silicone on a clean, dry, dust- and grease-free surface. The material to be glued must be strong enough to hold the weight. Clean the parts to be glued thoroughly. Primer is not necessary. Apply Black Seal Silicone to one of the adhesive surfaces and press both parts directly on top of each other. Remove excess material immediately. Mechanically clean tools immediately or after curing.

#### TECHNICAL DETAILS

Colour: black

Temperature range: -50 °C to +250 °C

Contents: 12 x 200 ml/carton

